



Turnbar Tower/Roller Assembly
Accurately guides Poly Tags as they are fed through the tool

Tough Poly Tags
Resist fading and readily accept thermal transfer imprinting

Rugged Protective Roll Housing
Holds up to 20 cm rolls of Poly Tags

Durable Housing
Constructed of a one-piece anodized billet aluminum

Anti-Slip Grip
Helps prevent hands from slipping

Tether Ring
Helps reduce fatigue when used with a shock cord

Easy-Action Trigger

Quick-Release Tag Guide
Opens smoothly with Slide Block and provides easy access to tags

Tag Cutter & Stapler
Precisely cuts the tags and staples them in one continuous motion

TTAC TU-TAGGER

PNEUMATIC TAG STAPLER

FOR OUTDOORS AND INDOORS USE

Article nr. 12030

The TU-TAGGER uses compressed air to apply tags at a rate of over 100 tags per minute. Your operator simply places the tool against the end of a piece of lumber and pulls the trigger. The TU-TAGGER automatically staples the tag to the lumber, cuts it, and then feeds the next tag into position. A special feed mechanism increases speed while decreasing chances for tag jam up.

Preserve your cutting edges with plastic staples

Do you find yourself wondering if that staple is aluminium or steel? Worry no more – plastic staples are always friendly to cutting tools. The TU-TAGGER is exclusively made for plastic staples.

Technical data

Weight 2.5 kg (empty)
2.9 kg (loaded)

Staple leg length 7–16 mm (1/4"–1/2")

Staple type TU-TAGGER accepts the Titac TU line of staples. Visit titac.com for more info.

Rec. pressure 5 — 6.2 bar (75—90 psi)
Max pressure 6.2 bar (90 psi)

Air consumption 85 litre per minute of continual operation at 6 bar



Plasa Fastening AB
Verkstadsgatan 16
73338 Sala, Sweden

Tel: +46-(0)224-19191
Email: info@plasafastening.com
Web: www.plasafastening.com

Authorized reseller

